Stude	nt Name	:		
Teacher:		Date:		
District:		Rowan		
Assessment: Description: Form:		9_12 T and I IC62 - Drafting - Architr II Test 1 Unit C - Floorplans - Test 1		
			501	
		1. Na	ame a co	overed walkway with open sides between two different parts of a structure.
A.	Lanai			
В.	Breeze	eway		
C.	Porch Patio			
D.	ratio			
2. W	hat is th	e bathroom fixture designed for washing hands and face?		
Α.	Bidet			
B.	Laund			
C.	Lavato			
D.	Water	closet		
3. W	hat are	vertical and horizontal members between window and door units?		
A.	Jambs			
В.	Munti			
C.	Mullio	ons		
D.	Sills			
4. Na	ame the	room designed specifically for washing, drying, folding, and ironing clothes.		
A.	Bedroo	om		
В.	Utility	Room		
C.	Lanai			
D.	Laund	ry		

5. N	ame the lines used to show where an object is to be sectioned.
A.	Cutting plane
В.	Hidden
C.	Center
D.	Phantom be sectioned.
6. Na	ame the ground-level exterior entertaining area that is made of concrete, stone, brick, or treated wood.
Α.	Porch
B.	Breezeway
C.	Portico
D.	Patio
7. W	hat is the masonry wall formed with two wythes with air space between each face?
A.	Cavity wall
В.	Plumbing wall
C.	Typical wall section
D.	Casing
8. N	ame the horizontal member that rests on the foundation wall to support other wood members.
Α.	Header
B.	Jamb
C.	Mud Sill
D.	Swing
9. W	That is the inside trim board placed below a window sill?
Α.	Casing
B.	Alcove
C.	Apron
D.	Header

10. Name the building parts that have been preassembled either in a plant or on-site.	
Α.	Sills
В.	Jambs
C.	Mullions
D.	Modular
11. W	hat is the decorative trim that covers the space between the jamb and a rough opening?
Α.	Sill
В.	Casing
C.	Jamb
D.	Mullions
12. W	What members divide window glass into smaller panes?
A.	Muntins
В.	Mullions
C.	Jamb
D.	Sill
13. N	ame the room that includes space for laundry as well as long-term storage of food.
Α.	Utility Room
В.	Laundry Room
C.	Lanai
D.	Pantry well as long-term storage of food.
14. N	ame the exterior floor supported on at least two opposing sides by adjoining structures, piers, or posts.
A.	Lanai
В.	Patio
C.	Breezeway
D.	Deck

15. Name a small room adjoining a larger room often separated by an archway or cased opening.	
A.	Alcove
В.	Apron
C.	Casing
D.	Compartment separated by an archway or cased opening.
16. N	ame the water-flushing plumbing fixture designed to receive and discharge human waste.
A.	Bidet
В.	Shower
C.	Lavatory
D.	Water closet
17. N	ame the member that extends vertically in a door or window opening.
A.	Side jamb
В.	Head jamb
C.	Sill
D.	Casing
18. W	hat walls in a building are designed for plumbing pipes to be installed?
A.	Compartmentalized wall
В.	Typical wall
C.	Cavity wall
D.	Plumbing wall
19. W	hat term describes a water closet that is partitioned off from other bathroom fixtures?
A.	Closed
В.	Compartmentalized
C.	Lavatory
D.	Water closet

20. What is the beveled member directly under a door?	
A.	Header
В.	Jamb
C.	Sill
D.	Threshold
21. W	That is a term used in building codes to describe access?
Α.	Casing
В.	Compartmentalized
C.	Egress
D.	Door
22. Ir	what type of design are rooms in cubicles with little opportunity for overflow into other rooms?
A.	Closed plan
В.	Open plan
C.	Bedrooms
D.	Compartmentalized
23. W	hat is the minimum depth for a wall-type wardrobe closet?
Α.	18"
В.	24"
C.	36"
D.	48"
24. W	hat relationship is kitchen design and efficiency based upon?
A.	Two centers
В.	Three centers
C.	Four centers
D.	Its location with respect to the dining room location

B.	3
C.	4
D.	5
26. A	minimum, acceptable size for a double car garage should be:
A.	10' × 18'.
B.	$14' \times 20'$.
C.	$20' \times 20'$.
D.	$20' \times 30'$.
27. W	hen the water closet is separated from the bathroom by walls and doors, it is called a/an:
A.	Compartmented bath.
В.	Closed bath.
C.	Open bath.
D.	Separated bath.
28. B	athrooms must have:
A.	Natural ventilation or an exhaust fan.
В.	A shower.
C.	A tub.
D.	Ceramic tile floors.
29. B	edroom doors:
A.	Should swing out, into the hall.
В.	When possible, should be placed in the center of the wall.
C.	Must be a minimum of 3'-0" wide.
D.	Should be sized to allow for furniture movement.

25. What is the number of bedrooms in a typical residence?

A. 2

A.	Closet.
В.	Lavatory.
C.	Dressing room.
D.	Make-up counter.
31. T	he L-shape kitchen is located along:
A.	One wall.
В.	Two walls.
C.	Three walls.
D.	Four walls.
32. T	he kitchen work triangle, with all sides added together, should not exceed:
A.	18' – 0".
В.	20' - 0".
C.	22' – 0".
D.	25' – 0".
33. A	covered area leading into a building is a:
A.	Deck.
В.	Foyer.
C.	Garage.
D.	Porch.
34. A	n enclosed area designed to protect an automobile is a:
A.	Breezeway.
В.	Carport.
C.	Garage.
D.	Parking deck.

30. The foyer typically includes a:

35. What is the recommended depth for wall cabinets?
A. 12" to 18"
B. 19" to 22"
C. 23" to 24"
D. 24" to 36"
36. When designing the dining room, take into consideration the:
A. Exterior view.
B. Location of the bathroom.
C. Size of the Great Room.
D. Size of the kitchen.
37. A "half bath" would include a:
A. Shower, water closet, and lavatory.
B. Tub, water closet, and lavatory.
C. Water closet and lavatory.
D. Any of the above.
38. A room for the laundry appliances is often referred to as the:
A. Dressing room.
B. Washing room.
C. Lanai.
D. Utility room.
39. What type of kitchen has cabinets on two adjacent walls?
A. Corridor
11. CULLINUI

A. B.

H-shaped

C. L-shapedD. Peninsula

40. When meeting with a client, what information should be obtained?	
A.	Design needs or requirement list
В.	The kind of car they drive
C.	Their financial status
D.	It is not necessary to meet with a client.
41. A	ttic space used as living space is found in a:
A.	Two-story house.
B.	Ranch style house.
C.	One-story house.
D.	One and one-half story house.
42. A	covered area that provides protection from the weather between a house and a garage is called a:
A.	Breezeway.
В.	Deck.
C.	Patio.
D.	Stoop.
43. W	Which of the following rooms would be located in the "service area" of a residence?
Α.	Dining room
В.	Great room
C.	Foyer
D.	Kitchen
44. A	listing of rooms in the "sleeping area" of the house might include the:
A.	Bathroom.
B.	Foyer.
C.	Pantry.
D.	Kitchen.

45. Grouping areas of the home are sometimes referred to as:A. Planning.B. Room layout.

D. Zanina

Traffic flow.

D. Zoning.

46. What is the conventionally accepted depth of a linen closet?

- A. 1'-0"
- B. 1'-6"
- C. 2'-0"
- D. 3'-0"

47. The term "foyer" applies to a/an:

- A. Courtyard.
- B. Entry hall.
- C. Interior garden with skylights.
- D. Outside walk covered by a roof.

48. An "open" floor plan:

- A. Is most often found in traditional or period homes.
- B. Is associated with the sleeping area of the house.
- C. May combine several spaces (rooms) into one area.
- D. Provides room-to-room access through small door openings.

49. The one and one-half story house:

- A. Requires a larger lot than a one-story house.
- B. Has a second floor with less square footage than the first floor.
- C. Is very popular with older home buyers.
- D. Is more expensive to build than the two-story house.

50. Which of the following rooms would NOT be located in the "sleeping area"?

- A. Bathroom
- B. Bedroom
- C. Closet
- D. Dining